

RES-XR6 3U

14" Deep, 3 Drive, Front I/O Rugged Rackmount Server

- Up to two Intel Xeon Scalable Processors with 28 cores
- Up to 2TB DDR4 ECC Memory
- Up to 90TB of Storage and 6 PCIe 3.0 cards
- MIL-STD: 810G, 901D, 167-1, 461



A part of the *EnterpriseSeries™*, Mercury's RES-XR6 3U Server employs the latest Intel® Xeon® Scalable processors to accelerate compute intensive workloads for applications such as signal intelligence, cryptography, AI, surveillance, sensor fusion, analytics, communications, and audio/video processing.

Accelerated Cloud Computing

Featuring up to two Intel® Xeon® Scalable processors with AVX512, 2TB DDR4 ECC memory, 90TB of storage in three disk drives, expansion slots, and enhanced reliability features, the RES-XR6 3U delivers superior workload-optimized performance and hardware-enhanced security for mission critical applications.

Designed for the Field

The system incorporates advanced thermal and mechanical design features to provide superior resilience to shock, vibration, dust, sand, and temperature extremes. Dual redundant, hot swappable AC or DC power supplies provide high availability while a specially designed dust cover and new memory retention + vibration dampeners offer users extra security on the move.

Space Optimized Scalability

Optimized for size, weight, and power (SWaP), the system weighs only 29lbs, is 14" deep, and meets military environmental specifications. A robust array of high speed I/O, storage options, enhanced security features, and expansion choices allow users maximum flexibility for current and future system requirements.

Proven Performance

Mercury's EnterpriseSeries RES Servers are trusted worldwide for their high-performance, long life cycles, thermal resiliency, compatibility with industry standards, and SWaP optimization. With the latest Intel core-count processors and configurable I/O, RES servers are ideally suited to next-gen radar, mission, advanced simulation, command, control, and battle management processing mission critical applications.

Your Reliable Teammate

With over 30 years of technical expertise, Mercury Systems works closely with customers to design computing solutions that are easy to integrate, affordable, and reliable for years to come.

Mercury Systems is a leading commercial provider of secure sensor and safety-critical processing subsystems. Optimized for customer and mission success, Mercury's solutions power a wide variety of critical defense and intelligence programs.



ACQUIRE



DIGITIZE



PROCESS



STORAGE



EXPLOIT



DISSEMINATE

Modified COTS Expertise

For customized space, environmental, and performance requirements email tms@mrscy.com

Technical Specifications

2 Intel® Xeon® Scalable Bronze, Silver, Gold, or Platinum CPUs
with up to 28 cores per processor
Up to 2TB memory with 8 DIMM slots

Management and Operating System

Windows®, Linux®, VMWARE® and other hypervisors
IPMI v2.0, Redfish option available
TPM 1.2 or 2.0 Support

Expansion and Modular Maintainability

Up to 6 PCIe 3.0 cards
2 PCIe 3.0 x16 Full Length Full Height (FLFH)
3 PCIe 3.0 x8 Full Length Full Height (FLFH)
1 PCIe 3.0 x4 Low Profile (LP)

Input/Output Versatility

Front Access

3 Removable, Hot Pluggable, 2.5" SATA/SAS3 drives, U.2 NVME option available
1 CD-RW/DVD-RW/BD-RW Drive (Blu-Ray optional)
1 Power Switch

Rear Access

2 1GbE (RJ45)
1 Dedicated Management Port (RJ45)
1 VGA Graphics Port
1 Serial Port (DB9) (optional)
1 CD-RW/DVD-RW/BD-RW Drive (optional)
1 Power Switch
2 USB 2.0
Additional USB 2.0/3.0 (Optional)

Power Supply Options

Single or Redundant 100/240 VAC
Single or Redundant 10-36 VDC
Single or Redundant 36-72 VDC
Single MIL-STD-461 Option

Environmental*

Operating

Temperature: 0°C to 50°C
Extended Temperature: -15°C to 65°C
Humidity: 8% to 95% (non-condensing)
Shock: 3 axis, 35g, 25ms
Vibration: 4.76Grms, 10Hz to 2000 Hz (SSD)

Non-Operating

Temperature: -40°C to 70°C
Humidity: 5% to 95% (non-condensing)

Additional Options

Shock Pins
Slide Rails

Mechanical

Height: 3U or 5.25" inches (133.35mm)
Width: 17 inches (432mm)
Depth: 14 inches (347.9mm)
Weight (Typical)*: 29 pounds (13.1kg)
19" rackmountable

* Mercury Systems designs all products to meet or exceed listed data sheet specifications. Some specifications including I/O profiles, weight, and thermal profiles are configuration dependent. Contact Mercury for information specific to your desired configuration requirements.



Innovation That Matters and the Mercury Systems logo are registered trademarks and EnterpriseSeries is a trademark of Mercury Systems, Inc. Other product and company names mentioned may be trademarks and/or registered trademarks of their respective holders. Mercury Systems, Inc. believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.

Copyright © 2020 Mercury Systems, Inc.

6572.01E-0720-DS-XR63U3drFIO

EXPID14653



INNOVATION THAT MATTERS®

MERCURY SYSTEMS

47200 Bayside Parkway • Fremont, CA 94538 USA
(510) 252-0870 • Fax (510) 490-5529

MERCURY SYSTEMS INTERNATIONAL

26 Avenue Jean Kuntzmann
Monbonnot-Saint-Martin • 38330 France
+33 608 419949