

RES-XR5 1.5U

18" Deep, Up to 9 Drives, Rear I/O Rugged Rack Mounted Server

- Up to two E5-2600 v3/v4 Series Intel® Xeon® processors
- Up to 2TB DDR4 ECC Memory
- Up to 150TB of Storage and 4 PCIe 3.0 cards
- MIL-STD: 810G, 901D, 167-1, 1474D, 740-2, 461F
- Manufactured in AS5553 compliant, AS9100D facilities

A part of the *EnterpriseSeries™*, Mercury's RES-XR5 1.5U Server employs E5-2600 v3/v4 series Intel® Xeon® processors to accelerate compute intensive workloads for applications such as signal intelligence, cryptography, AI, sensor fusion, analytics, communications, and audio/video processing.

Reliable Performance

Featuring up to two E5-2600 v3/v4 series Intel® Xeon® processors with AVX512, 2TB DDR4 ECC memory, 150TB of storage with up to nine disk drives, expansion slots, and enhanced reliability features, RES-XR5 1U delivers superior workload-optimized performance and hardware-enhanced security. Advanced thermal and mechanical design features provide superior resilience to shock, vibration, dust, sand, and temperature extremes. Hardware and firmware management ensures delivery of the same server configuration over multiple years.

Space Optimized Stealth and Flexibility

Quiet and optimized for size, weight, and power (SWaP), the system weighs only **23lbs**, is **18" deep**, and meets multiple military environmental specifications including **airborne and structural noise**. A robust array of high speed I/O, storage options, expansion choices, and security features allow users maximum flexibility for current and future system requirements.

Mercury Systems is a leading commercial provider of secure sensor and safety-critical processing subsystems. Optimized for customer and mission success, Mercury's solutions power a wide variety of critical defense and intelligence programs.

Enhanced for the Field

The system includes a system control module for remote management, a patented Aeroloc Baffle system for low airflow operations, **remote battery bypass** that enables BIOS battery replacement without system shutdown, a removable PCIe card cage to simplify sparing, and numerous enhancement options. Additional features, testing, and certifications are available upon customer request.

Proven Performance

Mercury's EnterpriseSeries RES Servers are trusted worldwide for their high-performance, **long life cycles**, thermal resiliency, compatibility with industry standards, and **SWaP optimization**. With the latest Intel core-count processors and configurable I/O, RES servers are ideally suited to next-gen radar, mission, advanced simulation, command, control, and battle management processing mission critical applications.

Your Reliable Teammate

With over 30 years of technical expertise, Mercury Systems works closely with customers to design computing solutions that are easy to integrate, affordable, and reliable for years to come.

Our AS5553 compliant, AS9100D and ISO9001 facilities maintain quality and compliance to meet customer expectations.



ACQUIRE



DIGITIZE



PROCESS



STORAGE



EXPLOIT



DISSEMINATE

Modified COTS Expertise

For customized space, environmental, and performance requirements email tms@mrchy.com

Technical Specifications

2 Intel® Xeon® E5-2600 v3/v4 Series CPUs with up to 22 cores per processor

Bronze, Silver, Gold, or Platinum

Up to 2TB 2400MHz memory

Patented Technologies

Memory stabilization

Aeroloc baffle system

System control module for remote management

Management and Operating System

Windows®, Linux®, VMWARE® and other hypervisors

IPMI v2.0, Redfish option available

TPM 1.2 or 2.0 Support

Expansion and Modular Maintainability

Up to 2 PCIe 3.0 x16 cards and 2 PCIe 3.0 x8 cards (full height, half length)

in removable card cage

Input/Output Versatility

Front Access

Up to 9 Removable, Hot Pluggable, 2.5" SATA/SAS3 drives, U.2 NVME option available

can configure with up to (4) 15mm and (1) 7mm or (9) 7mm (SATA) high drives

1 Power/Reset Switch

1 CFM Switch (optional)

1 Power On LED

2 USB 3.0 (optional)

1 Quick Change CMOS Battery

Rear Access

2 1GBaseT or 10GBaseT Ethernet Ports (RJ45)

4 USB 3.0

1 RS-232

1 IPMI 2.0 (RJ45)

1 VGA Graphic Port

Power Supply Options

Single 100/240V VAC (47/63Hz, 400Hz)

Single 10-36 VDC, 32 Amps

Single 36-72 VDC, 18 Amps

MIL-STD 461, 704F, 1399-300B

Additional Options

Front Door Filter

Slide Rails

CAC Card Reader

Read/Write Switches to prevent accidental rewrite

MIL-STD / Industrial Specifications

MIL-STD 810G

Shock: MIL-STD 901D Grade A, IEC 60068-2-27

EMI/RFI: MIL-STD 461F, CE102 standard

Vibration: MIL-STD 167-1, MIL-STD 810G, IEC 60068-2-64

Airborne Noise: MIL-STD 1474D

Structure Borne Noise: MIL-STD 740-2

Temperature: IEC 60068-2-2 test Bb, 60068-2-1 test Ab

Environmental*

Operating

Temperature: 0°C to 50°C

Extended Temperature: -15°C to 65°C

Humidity: 5% to 95% (non-condensing)

Shock: 3 axis, 35g, 25ms

Vibration: 4.76Grms, 4Hz to 2000 Hz (SSD)

Altitude: 10,000 ASL

Non-Operating

Temperature: -40°C to 80°C

Humidity: 5% to 95% (non-condensing)

Altitude: 40,000 ASL

Conformal Coating: IPC-CC 830 (optional)

Mechanical

Height: 1.5U or 2.625" inches (66.7mm)

Width: 17 inches (431.8mm)

Depth: 18 inches (457.2mm)

Weight (Typical)*:

Steel Chassis: 23lbs (10.4kg)

Cooling: Internal fan-cooled (rear vent) front to rear

19" rackmountable

* Mercury Systems designs all products to meet or exceed listed data sheet specifications. Some specifications including I/O profiles, weight, and thermal profiles are configuration dependent. Contact Mercury for information specific to your desired configuration requirements.

The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters, EnterpriseSeries. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice. Copyright © 2019 Mercury Systems, Inc. 6557.00E-0419-DS-XR5G1.5U10drRIOGRS1500,1502 EXPID14225